

Standard SureGuide Tube and Shaft Sizes - South Africa

| Item Code | Belt Width "D" | Bracket to Bracket "A" | Back to Back "B" | Roller Face "C" | Belt Width "D" | Maximum Load |
|---|----------------|------------------------|------------------|-----------------|----------------|--------------|
| | in mm | Stringer Length mm | Gauge Length mm | Length mm | In mm | in KG's |
| 30 Series (30mm diameter shaft) (Roller - 168mm) | | | | | | |
| SG45/30 | 450 | 686 | 546 | 512 | 450 | 550 |
| SG60/30 | 600 | 838 | 698 | 661 | 600 | 500 |
| SG75/30 | 750 | 990 | 850 | 812 | 750 | 420 |
| SG90/30 | 900 | 1144 | 1004 | 966 | 900 | 350 |
| SG100/30 | 1000 | 1254 | 1114 | 1060 | 1000 | 270 |
| SG105/30 | 1050 | 1296 | 1156 | 1119 | 1050 | 250 |
| SG120/30 | 1200 | 1448 | 1308 | 1270 | 1200 | 200 |
| SG135/30 | 1350 | 1600 | 1460 | 1422 | 1350 | 150 |
| 40 Series (40mm diameter shaft) (Roller - 209mm) | | | | | | |
| SG90/40 | 900 | 1144 | 1004 | 966 | 900 | 750 |
| SG105/40 | 1050 | 1296 | 1156 | 1119 | 1050 | 720 |
| SG120/40 | 1200 | 1448 | 1308 | 1270 | 1200 | 580 |
| SG135/40 | 1350 | 1600 | 1460 | 1422 | 1350 | 382 |
| SG140/40 | 1400 | 1700 | 1560 | 1450 | 1400 | 370 |
| SG150/40 | 1500 | 1752 | 1612 | 1574 | 1500 | 365 |
| SG165/40 | 1650 | 1904 | 1764 | 1726 | 1650 | 260 |
| SG180/40 | 1800 | 2058 | 1918 | 1878 | 1800 | 220 |
| 50 Series (50mm diameter shaft) (Roller - 235mm) | | | | | | |
| SG105/50 | 1050 | 1296 | 1156 | 1119 | 1050 | 820 |
| SG120/50 | 1200 | 1448 | 1308 | 1270 | 1200 | 780 |
| SG135/50 | 1350 | 1600 | 1460 | 1422 | 1350 | 750 |
| SG140/50 | 1400 | 1700 | 1560 | 1450 | 1400 | 670 |
| SG150/50 | 1500 | 1752 | 1612 | 1574 | 1500 | 620 |
| SG165/50 | 1650 | 1904 | 1764 | 1726 | 1650 | 600 |
| SG180/50 | 1800 | 2058 | 1918 | 1878 | 1800 | 500 |
| SG200/50 | 2000 | 2264 | 2120 | 2052 | 2000 | 450 |
| SG210/50 | 2100 | 2362 | 2222 | 2154 | 2100 | 400 |
| SG220/50 | 2200 | 2464 | 2320 | 2252 | 2200 | 350 |
| SG240/50 | 2400 | 2668 | 2528 | 2458 | 2400 | 300 |

